



Features:

- TTL-Compatible Driver
- Broad Operating Bandwidth
- Rugged Construction.
- Customization Is Available

Specifications

Electrical Specifications, TA = +25° C

Parameters	Min.	Typ.	Max.	Units
Frequency Range	0.5		40	GHz
Insertion Loss		8	10	dB
VSWR		2.5	3	
Isolation	50			dB
Switching Speed			100	nsec
CW RF Power, Operating			20	dBm
Material		Aluminum		
Finish		Gold Plating		
Input /Output Connector	2.92mm-Female / 2.92mm -Female (Removable)			

※ Switching speed is defined as 50% TTL to 90% RF (t-on) and 50% TTL to 10% RF (t-off).

Environmental Specifications

Operational Temperature (°C)	-45 ~ +85
Storage Temperature (°C)	-55 ~ +125
Vibration	25g rms (15 degree 2KHz)
Humidity	100% RH at 35c, 95%RH at 40 deg c
Shock	20G for 11msc

DC Bias: +5 V±0.5 V @ 400 mA max
-5 V±0.5 V @ 50 mA max


Absolute Maximum Ratings	
Biasing	+5 V , -5V
TTL Control Voltage	+5V/0V
Input RF power	+20dBm
Storage Temperature (°C)	-55 ~ +125

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Amwav reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Truth Table



Control Input TTL								Signal Path State
E8	E7	E6	E5	E4	E3	E2	E1	
1	1	1	1	1	1	1	0	J0-J1
1	1	1	1	1	1	0	1	J0-J2
1	1	1	1	1	0	1	1	J0-J3
1	1	1	1	0	1	1	1	J0-J4
1	1	1	0	1	1	1	1	J0-J5
1	1	0	1	1	1	1	1	J0-J6
1	0	1	1	1	1	1	1	J0-J7
0	1	1	1	1	1	1	1	J0-J8

Outline Drawing:



1. Dimensions are in mm [inches].
2. Tolerances: Outline drawing $\pm 0.1\text{mm}$
Hole $\pm 0.1\text{mm}$.

Test Curve:



AMWAV Technology, Ltd.

Website: www.amwav.com

E-mail: sales@amwav.com

Tel/Fax: +86 02887492975

Part No.

AWSP8TA-0.5-40GA

Notes:

All SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME

Scale

1:1

DWG No.

REV

A