



AWPD4-2-40GA

Your RF& Microwave Components Source

Features:

- Broadband
- High Reliability, High Isolation
- Small Size
- Cost Efficient

Description:

The power/divider combiner offered by AMWAV are designed for both commercial and military applications.


Specifications

Parameters	Min.	Тур.	Max.	Units
Frequency range	2	-	40	GHz
Isolation	16	-	-	dB
Insertion Loss	-	2.6	3.0	dB
VSWR input			2.0	
VSWR output			1.6	
Phase Unbalance			\pm 10	o
Amplitude Unbalance			±0.5	dB
Forward Power			20	W cw
Reverse Power			1	W cw
Operating Temperature Range	-55	-	+85	°C
Impedance	-	50	-	Ω
Connectors	2.92-Female			
Finish	Gray Paint			


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Amway reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.


Website: www.amwav.com Email: sales@amwav.com Tel/Fax: +86 02887492975

Outline Drawing:



Test Curve:







E-mail: sales@amwav.com Tel: +86 02887492975 TITLE

AWPD4-2-40GA

Notes:

- 1. All specifications are subject to change without notice at any time
- 2. DIMENSIONS ARE IN MM.

Scale	DWG No.	REV	
1/1		Α	